



RaW Wolf®

60+ YEARS SERVICE TO THE NATION

PRODUCT CATALOGUE

Power Tools | Farm Equipment | Air Tools | Welding Equipment | Motors | Accessories

About **Ralli Wolf**[®]

Ralli Wolf, one of the torchbearers in power tool production in India, started its journey more than 60 years ago in collaboration with Wolf UK. Six decades down the line, the company is firmly committed to providing complete, high-quality solutions in a wide variety of segments such as **Power Tools, Farm Equipment, Pneumatic Tools, Welding Equipment, Motors, and Accessories**.

Production is done at Ralli Wolf's state-of-the-art plant at Ahmednagar, Maharashtra, India, equipped with the latest technology and bolstered by a talented engineering support. This combination of innovative technology and professional expertise delivers products of exceptional performance and reliability.

At the core of Ralli Wolf's philosophy is a constant emphasis on innovation, design excellence, technology leadership, and hassle-free implementation. With a strong pan-India footprint, the company has the support of a committed sales and service network at 30 strategic locations, offering unparalleled customer care and accessibility throughout the nation.



CORDLESS TOOLS**DRIVER DRILL**
MODEL NO : RCD12V

Double Battery

Rated Power	:	12v
Speed	:	0-400/0-1450 r/min
Drill Capacity (Steel)	:	10mm
Drill Capacity (Wood)	:	15mm
Net. Weight	:	0.8 Kg

**DRIVER DRILL**
MODEL NO : RCD21V

Double Battery

Rated Power	:	21v
Speed	:	0-400/0-1450 r/min
Drill Capacity (Steel)	:	10mm
Drill Capacity (Wood)	:	15mm
Net. Weight	:	1.1 Kg

**IMPACT WRENCH**
MODEL NO : RIW21V

Double Battery

Rated Power	:	21v
Speed	:	2060 r.p.m
Bolt Capacity	:	Upto 32mm
Battery	:	4000 mAh
Net. Weight	:	1.62 Kg

**BRUSHLESS ANGLE GRINDER**
MODEL NO : RCG100 | RCG125

Double Battery

RCG100	RCG125	
Voltage	:	21V
Battery	:	4 Ah
Disc Dia	:	100mm
No Load Speed	:	5000-9000 r.p.m
Approx. Weight	:	5.15 Kg
	:	5.35 Kg

**AIR INFLATOR**
MODEL NO : RCAI-150

Rated Power	:	11.1V
Battery Capacity	:	1800mAh x 3pcs
Air Flow	:	20L/min
Max Pressure	:	150PSI
Inflate Time	:	7min (195.55/R15)
Charging Time	:	3HRS
Battery Life Time	:	500 cycles

**VACUUM CLEANER**
MODEL NO : RCVC-12FA

Rated Power	:	90W
Voltage	:	11.1V
Built in Battery Type	:	Li ion
Battery Capacity	:	2000mAh x 3pcs
High Speed	:	13-15 Mins
Charging Time	:	4-5 hrs
Dust Cup Capacity	:	0.40L

**JUMP STARTER & INFLATOR (2-IN-1)**
MODEL NO : RJS-8000

NEW

Rated Power	:	14.8V
Capacity	:	8000 mAh (4x2000mah)
Air Pressure	:	0.2-10.3 Bar/ 3-150Psi
Air Hose	:	30cm
Cylinder Diameter	:	19mm

*"I never dreamed about success. I worked for it."***ELECTRIC DRILLS****ROTARY DRILL**
MODEL NO : RW10

Without Chuck

Rated Power	:	650 watts
Speed	:	1250 r.p.m
Capacity	:	10mm
Net. Weight	:	1.7 kg

**PLAIN DRILL**
MODEL NO : RD10

Rated Power	:	500 watts
Voltage	:	230V 50Hz
Speed	:	0-2800r/min
Capacity	:	10mm

**MODEL NO : RED10**

NEW

Rated Power	:	450 Watts
Rated Frequency	:	50 Hz
Speed	:	0-3000 r.p.m
Capacity	:	10mm

**COMPACT DRILL**
MODEL NO : 12110

Rated Power	:	600 watts
Speed	:	0-2500 r.p.m
Drill Capacity (Steel)	:	10mm
Drill Capacity (Wood)	:	25mm



SCREW DRIVER DRILL MODEL NO : RW-SD10

Voltage	:	230V 50Hz
Rated Power	:	400 watts
Switch	:	Variable & Reversible
No Load Speed	:	0-750r/min
Approx. Weight	:	1.3 Kg



MODEL NO : 16130

Rated Power	:	600 Watts
Speed	:	0-2650 r.p.m
Capacity	:	13mm
Net. Weight	:	1.9 kg



MODEL NO : 18130

Rated Power	:	700 Watts
Speed	:	0-2800 r.p.m
Capacity	:	13mm
Net. Weight	:	2.0 kg



MODEL NO : RDK13-KIT

Rated Power	:	500 Watts
Speed	:	0-3000 r.p.m
Capacity	:	13mm
Net. Weight	:	4 kg



IMPACT DRILL MODEL NO : RW13

Rated Power	:	650 Watts
Speed	:	1800 r.p.m
Capacity	:	13mm
Net. Weight	:	2 kg (Supply is without chuck)



IMPACT DRIVER MODEL NO : RID6

Voltage	:	230V 50HZ
Rated Power	:	230W
Driving Shank	:	6.35mm
No Load Speed	:	0-3600 RPM
Net. Weight	:	1.3 KG



ELECTRIC IMPACT WRENCH MODEL NO : RW300-I

Rated Power	:	450W
No Load Speed	:	2600 RPM
Torque	:	300NM
Approx. Weight	:	3.3 KG



"Stop! Think! I'm here to stand up for your safety"

DIE GRINDER

MODEL NO : RDG25

Rated Power	:	420 watts
Capacity	:	6mm (collet)
Speed	:	25000 r.p.m.
Net Weight	:	1.9 Kg



MODEL NO : RDG600

Rated Power	:	550 watts
Capacity	:	6mm (collet)
Speed	:	27000 r.p.m.
Net Weight	:	1.5 Kg



MODEL NO : RDG-60

NEW

Rated Power	:	600 watts
Capacity	:	6mm (collet)
Speed	:	29000 r.p.m.
Net Weight	:	1.8 Kg



"Zero compromise towards safety"

4" ANGLE GRINDER



MODEL NO : RG6-100

Disc Dia : 100mm
Watts Input (full load) : 750 watts
Disc Size : 100x16x6mm
Speed : 11000 r.p.m.
Net Weight : 1.7 Kg



MODEL NO : 25100

Disc Dia : 100mm
Watts Input (full load) : 800 watts
Disc Size : 100x16x5.5mm
Speed : 11000 r.p.m.
Net Weight : 1.6 Kg



MODEL NO : RF9-100

Disc Dia : 100mm
Watts Input (full load) : 900 watts
Disc Size : 100x16x5.5mm
Speed : 11000 r.p.m.
Net Weight : 1.7 Kg



MODEL NO : RG9-100

NEW

Disc Dia : 100mm
Watts Input (full load) : 900 watts
Disc Size : 100x16x6mm
Speed : 11000 r.p.m.
Net Weight : 1.75 Kg



MODEL NO : AG100

Disc Dia : 100mm
Watts Input (full load) : 1100 watts
Disc Size : 100x16x6mm
Speed : 11000 r.p.m.
Net Weight : 2 Kg



MODEL NO : 45100 | 45125H

Improved

Disc Dia	: 100mm	125mm
Watts Input (full load)	: 850 watts	850 watts
Disc Size	: 100x16x5mm	125x22.5x5.5mm
Speed	: 11000 r.p.m.	11000 r.p.m.
Net Weight	: 1.6 Kg	1.8 Kg

5" ANGLE GRINDER



MODEL NO : 35135

Disc Dia : 125mm
Watts Input (full load) : 1350 watts
Disc Size : 125x22x5.5mm
Speed : 9000 r.p.m.
Net Weight : 3.1 Kg



MODEL NO : AG125

Disc Dia : 125mm
Watts Input (full load) : 1020 watts
Disc Size : 125x22x6mm
Speed : 10500 r.p.m.
Net Weight : 2 Kg



MODEL NO : 60145

Disc Dia : 125mm
Watts Input (full load) : 1400 watts
Disc Size : 125x22x5mm
Speed : 3000-11000 r.p.m.
Net Weight : 2.2 Kg



Special Features : • Electronic overload protection • Soft start • Slide type deadman switch



"Whether you think you can or think you can't, you're right."

7" ANGLE GRINDER



MODEL NO : AG180

Disc Dia : 180mm
Watts Input (full load) : 2400 watts
Disc Size : 180x22x5.5mm
Speed : 8500 r.p.m.
Net Weight : 5.1 Kg



MODEL NO : RG22-180

NEW

Disc Dia : 180mm
Watts Input (full load) : 2200 watts
Disc Size : 180x22x5.5mm
Speed : 8400 r.p.m.
Net Weight : 5.5 Kg



**MODEL NO : RG26-180****NEW**

Disc Dia	:	180mm
Watts Input (full load)	:	2400 watts
Disc Size	:	180x22x5.5mm
Speed	:	8400 r.p.m.
Net Weight	:	5.5 Kg

**MODEL NO : RG7-30**

Disc Dia	:	180mm
Watts Input (full load)	:	3000 watts
Disc Size	:	180x22x5.5mm
Speed	:	6800 r.p.m.
Net Weight	:	7 Kg

9" ANGLE GRINDER**MODEL NO : AG230**

Disc Dia	:	230mm
Watts Input (full load)	:	2400 watts
Disc Size	:	230x22x5.5mm
Speed	:	6800 r.p.m.
Net Weight	:	5.1 Kg

**MODEL NO : RG9-30**

Disc Dia	:	230mm
Watts Input (full load)	:	3000 watts
Disc Size	:	230x22x5.5mm
Speed	:	6500 r.p.m.
Net Weight	:	7 Kg



ROTARY HAMMER**ROTARY HAMMER
MODEL NO : RW-22H**

Rated Power	:	650 watts
Current	:	2.9 Amps
Energy	:	1.5 Joule
Speed	:	0-850 r.p.m/min
Net Weight	:	2.7 kg

**ROTARY HAMMER
MODEL NO : RW22-3M**

Rated Power	:	1350 watts
Current	:	2.55 Amps
Energy	:	4.5 Joule
Speed	:	900 r.p.m
Net Weight	:	4.5 kg

**ROTARY HAMMER
MODEL NO : RW-26H**

Rated Power	:	800 watts
Current	:	3.4 Amps
Energy	:	3 Joule
Speed	:	0-1100 r.p.m/min
Net Weight	:	3.1 kg

**ROTARY HAMMER
MODEL NO : RW2-32H**

Rated Power	:	1150 watts
Current	:	4.89Amps
Energy	:	6.0 Joule
Speed	:	900 r.p.m
Net Weight	:	4.5 Kg

DEMOLITION HAMMER**DEMOLITION HAMMER
MODEL NO : RW-5EH**

Rated Power	:	1200 watts
Impact Rate	:	1400 BPM
Energy	:	10 Joule
Speed	:	0-4100 r.p.m/min
Net Weight	:	6.07 kg

**DEMOLITION HAMMER
MODEL NO : RW-11H**

NEW

Rated Voltage	:	235V AC
Input power	:	1500W
InputEnergy	:	35 Joule
Impact Rates	:	900 ~ 19000 B.P.M.
Net Weight	:	11 kg

**DEMOLITION HAMMER
MODEL NO : RW-15H**

Rated Power	:	1500 watts
Impact Rate	:	1850 BPM
Energy	:	45 Joule
Current	:	6.38 Amps
Net Weight	:	15 kg



**"The bad news is time flies.
The good news is you're
the pilot."**

CONSTRUCTION TOOLS**CONCRETE VIBRATOR
MODEL NO : RW-CV35-3**

Rated Power	:	850 watts
Voltage	:	230V 50Hz
Vibration Rod	:	35mm 1.5m
Speed	:	4000 r.p.m
Current	:	3.7 Amps
Net Weight	:	2 kg

**CONCRETE VIBRATOR
MODEL NO : RW-CV35-3**

Rated Power	:	1100 watts
Voltage	:	230V 50Hz
Vibration Rod Dia	:	35mm 3m
Speed	:	4400 r.p.m
Current	:	5 Amps
Net Weight	:	2.4 kg

**PAINT MIXER
MODEL NO : RPM16**

Voltage	:	230V 50Hz
Rated Power	:	1000W
Speed	:	1000r/min
Spindle Size	:	M12
Current	:	4.5 Amps.
Net. Weight	:	3.5 Kg

**PRESSURE WASHER
MODEL NO : RHP120**

NEW

Rated Voltage	:	235V AC
Watts Input (Full Load)	:	1600W
Flow Rate	:	480L/H
Motor Type	:	Induction Motor
Max Pressure	:	120 Bar
Approx. Weight (kg)	:	6 Kg



PRESSURE WASHER
MODEL NO : RHP 130

Motor Type	:	Induction
Max Pressure	:	130 Bar
Flow Rate	:	480 L/H
Voltage	:	235 V AC
Watt	:	1600W
Net. Weight	:	12 Kg.



WALL SANDER
MODEL NO : RWS 180

Voltage	:	230V 50Hz
Rated Power	:	850W
Speed	:	900-2100 RPM
Insulation	:	Double Insulated
Diameter of Disc	:	180mm
Net. Weight	:	2.7Kg



WALL CHASER
MODEL NO : RWC 133

Voltage	:	230V 50Hz
Rated Power	:	2700W
No Load Speed	:	6200 RPM
Max Blade Diameter	:	133mm
Full Load Current	:	11.7 AMPS
Net. Weight	:	6.2 Kg



"Work smart from the start."

DIAMOND CORE DRILL



MODEL NO : RDD110

Rated Power	:	2080 watts
Voltage	:	230V
Speed	:	2100 r.p.m
Drill	:	12-110mm



MODEL NO : RDD200 | RDD250

	RDD200	RDD250
Rated Power	:	3900 watts
Voltage	:	230V 50Hz
Speed	:	580 r.p.m
Drill	:	205mm
Net. Weight	:	20.5 Kg
		4250 watts
		220V AC
		560rpm
		255mm
		24Kg

CHOP SAW



MODEL NO : RW14E

Cutting Capacity	:	355mm
Rated Power	:	2300 Watts
No Load Speed	:	3900 r.p.m
Net. Weight	:	17.2 kg.



MODEL NO : RC14D

D Handle

Cutting Capacity	:	355mm
Rated Power	:	2600 Watts
No Load Speed	:	3900 r.p.m
Net. Weight	:	18 kg

MITER SAW



MODEL NO : RMS255

NEW

Rated Power	:	2200 Watts
Base Size	:	47x30cm
Speed	:	5000 rpm
Approx. Weight	:	12.3kg



**"Knowing is not enough
we must apply. Willing is
not enough; We must do"**

MARBLE CUTTER



MODEL NO : RW125N

NEW

Rated Power	:	235V 50Hz 1400 W
Blade Diameter	:	125mm
Speed	:	13000 r.p.m
Current	:	5.5 Amps
Net. Weight	:	3.42 Kg



MODEL NO : RW4

Rated Power	:	235 V AC
Max. Blade Diameter	:	110 mm
Watts	:	1100W
Speed	:	13000 r.p.m.
Current	:	4.5 Amps
Net Weight	:	3.2 kg

**MODEL NO : RW4-SB**

Rated Voltage	:	235V AC
watts Input (Full Load)	:	1200W
No Load Speed	:	11000 rpm/min
Insulation	:	Double Insulation
Approx Weight	:	3.0 Kg

**MODEL NO : RC4HD**

Rated Power	:	1200 watts
Wheel Diameter	:	110mm
Voltage	:	230V
Speed	:	11000r/min
Current	:	5.2 Amps
Net Weight	:	2.9 kg

WOOD WORKING TOOLS**PLANER****MODEL NO : RP 500**

Rated Power	:	500Watts
Rated Voltage	:	220/240V AC
No-Load Speed	:	17000 RPM
Net. Weight	:	2.6 Kg

**CIRCULAR SAW****MODEL NO : RS 180 NEW**

Voltage	:	220V
Rated Power	:	1200W 50Hz
Cutting Capacity (90°)	:	84mm
Cutting Capacity (45°)	:	65mm
Blade Dia	:	185mm
Speed	:	5300 r.p.m
Current	:	5.9A
Net. Weight	:	4.3 Kg. (without Blade)

**CIRCULAR SAW****MODEL NO : RS 185**

Voltage	:	220V
Rated Power	:	1400W 50Hz
Cutting Capacity (90°)	:	84mm
Cutting Capacity (45°)	:	65mm
Blade Dia	:	185mm
Speed	:	5500 r.p.m
Current	:	5.9A
Net. Weight	:	4.3 Kg. (without Blade)

**ROUTER****MODEL NO : RW-RT12**

Rated Power	:	1800 watts
Voltage	:	230V 50Hz
Speed	:	23000 r.p.m
Cutter Size	:	8-12mm
Current	:	7.8 Amps
Net Weight	:	4.1 kg

**JIG SAW****MODEL NO : RJS 60**

Rated Power	:	600 watts
Voltage	:	235V 50Hz
Strokes/min	:	500-3000 spm
Cutting Capacity	:	60mm
Current	:	2.55 Amps
Net Weight	:	2.50 kg

**TRIMMER****MODEL NO : RT6 | RT60**

Voltage	:	230V	220V
Rated Power	:	600W 50Hz	500W 50Hz
Speed	:	30000 r.p.m.	30000 r.p.m.
Mandrel Connection	:	6mm/6.35mm	6mm/6.35mm
Current	:	2.6Amps	2Amps
Net. Weight	:	1.9 Kg	1.7 kg

HEAT GUN**MODEL NO : RG 2100**

Rated Power	:	2100W 50Hz
Full Load Current	:	8.5Amps.
Temperature	:	1-350° C 2-550° C
Net. Weight	:	0.6 kg.

**MODEL NO : RHG 1600**

Voltage	:	AC 235V 50Hz
Rated Power	:	1600W
Full Load Current	:	8.5Amps.
Temperature	:	350° C 250 L/Min 550° C 550 L/Min
Net. Weight	:	0.650 kg.

ELECTRIC BLOWER**MODEL NO : RB500**

Rated Power	:	235V AC
Watts	:	600W
Speed	:	16000 r.p.m
Current	:	2.55 Amps
Air Volume	:	3.8m³/min
Net. Weight	:	1.8 Kg

**MODEL NO : RB60V**

Rated Power	:	235V AC
Watts	:	600W
Speed	:	6000-16000 r.p.m
Current	:	2.55 Amps
Air Volume	:	3.8m³/min
Net. Weight	:	1.8 Kg

**MODEL NO : RB50-S**

Rated Power	:	235V AC
Watts	:	600W
Speed	:	16000 r.p.m
Current	:	2.55 Amps
Air Volume	:	3.2m³/min
Net. Weight	:	1.8 Kg

**MODEL NO : RB500 PRO**

Rated Power	:	235V AC
Watts	:	600W
Speed	:	16000 r.p.m
Current	:	2.55 Amps
Air Volume	:	3.8m³/min
Net. Weight	:	1.6 Kg

VACUUM CLEANER**VACUUM CLEANER****MODEL NO : RVC-12L**

Rated Power	:	1200w
Air Flow	:	26Ltr/Sec
Filtration type	:	HEPA
Suction Power	:	≥18kpa
Dust Capacity	:	12L
Net. Weight	:	3.5KGS

CAR POLISHER**MODEL NO : RCP 180**

Voltage	:	230V 50Hz
Rated Power	:	1400W
Pad size	:	180mm
Speed	:	600-3000 RPM

Approx. Weight : 3kg

AIR COMPRESSOR**MODEL NO : RC 30-OF**

Capacity	:	167L/min
Air flow	:	100L/min
Voltage	:	220V/50Hz
Rated Power	:	2Hp
Tank	:	30L
Lubrication	:	Oil Free
Net. Weight	:	21.5KGS

**MODEL NO : RC 50**

Capacity	:	135L/min
Air flow	:	203L/min
Voltage	:	220V/50Hz
Rated Power	:	2.5HP
Tank	:	50 LTR
Lubrication	:	Oil
Net. Weight	:	27.5kgs



MAGNETIC CORE DRILL



MODEL NO : YUVA 40

Rated Voltage	:	220V 50Hz
Rated Power	:	1150 Watts
Max Core Drill Capacity	:	40 x 50mm
Max Twist Drill	:	upto 13mm
No Load Speed	:	750 RPM
Magnetic Adhesion	:	10000 N
Net. Weight	:	15Kgs



MODEL NO : COMMANDO 40 S

Rated Voltage	:	230V
Rated Power	:	1100 watts
Capacity	:	40x50mm
Max Twist Drill Dia	:	13mm
No Load (RPM)	:	270-610 RPM
Magnetic Adhesion	:	8000 N
Net. Weight	:	13.7 kg



MODEL NO : MEGA 42

Variable Speed

Rated Voltage	:	220V 50Hz
Rated Power	:	1400 Watts
Max Core Drill Capacity	:	42 x 50mm
Max Twist Drill	:	13mm
No Load Speed	:	100 - 700 RPM
Magnetic Adhesion	:	12000 N
Net. Weight	:	13Kgs



MODEL NO : COMMANDO 50

Rated Voltage	:	230V
Rated Power	:	1500 watts
Max Twist Drill Dia	:	23mm
No Load (RPM)	:	100-500 RPM
Magnetic Adhesion	:	13500 N
Net. Weight	:	15.8 kg



MODEL NO : MEGA 50

Rated Voltage	:	220V 50Hz
Rated Power	:	1400 Watts
Max Core Drill Capacity	:	50 x 50mm
Max Twist Drill Capacity	:	23mm
No Load Speed	:	100 - 470 RPM
Spindle	:	MT2
Magnetic Adhesion	:	16500 N
Net. Weight	:	19Kgs



MODEL NO : NW50S

Voltage	:	235 V
Rated Power	:	1600 watts
No load RPM	:	450 RPM
Max Core Drilling Capacity	:	50x50mm
Approx. Weight	:	31 Kg



MODEL NO : COMMANDO 50 LP

Rated Voltage	:	230V
Rated Power	:	1200 watts
Magnet Size	:	192x82mm
No Load (RPM)	:	250-500 RPM
Magnetic Adhesion	:	10000 N
Net. Weight	:	11 kg



MODEL NO : COMMANDO 50 PM

Rated Voltage	:	230V
Rated Power	:	1500 watts
Magnet Size	:	2770x190mm
Max Twist Drill	:	23mm
No Load (RPM)	:	100-500 RPM
Magnetic Holding Force	:	860 Kgs (8430N)
Net. Weight	:	18 kg



MODEL NO : COMMANDO 75

Rated Voltage	:	230V
Rated Power	:	1800 watts
Adaptor Size	:	MT3
No Load (RPM)	:	70-500 RPM
Capacity	:	75x75mm
Magnetic Adhesion	:	18500 N
Net. Weight	:	22.8 kg



MODEL NO : MEGA 80

NEW

Rated Voltage	:	230V 50Hz
Rated Power	:	1950W
Capacity	:	80x80mm
Max Twist Drill Dia	:	28mm
Speed	:	100-510RPM
Magnetic Adhesion	:	16700N
Net. Weight	:	18kg



MODEL NO : COMMANDO 100

Rated Voltage	:	230V
Rated Power	:	2000 watts
Adaptor Size	:	MT3
No Load (RPM)	:	45-700 RPM
Capacity	:	100x100mm
Magnetic Adhesion	:	20000 N
Net. Weight	:	22 kg



MODEL NO : MEGA 150

Rated Voltage	:	230V
Rated Power	:	3080 watts
Adaptor Size	:	MT4
No Load (RPM)	:	40-720 RPM
Capacity	:	150x150mm
Magnetic Adhesion	:	24500 N
Net. Weight	:	32 kg

METAL INDUSTRIAL DRILL



HEAVY DUTY DRILL MODEL NO : WDH | WDH12

	WDH	WDH12
Capacity	: 13 – 23 mm	13 – 23 mm
Watts Input (full Load)	: 595 Watts	1200 Watts
No Load Speed	: 560 r.p.m.	450 r.p.m.
Approx Net Weight	: 7 kg.	7.2 kg.



TWO SPEED DRILL MODEL NO : TS3C

Rated Power	:	600 watts
Wheel Size	:	10mm 16mm
Speed	:	1380 r.p.m 560 r.p.m
Net Weight	:	5.4 kg



HEAVY DUTY DRILL MODEL NO : WDHC | WDHC12

	WDHC	WDHC12
Capacity	: 20 mm	20 mm
Watts Input (full Load)	: 595 Watts	1200 Watts
No Load Speed	: 560 r.p.m.	450 r.p.m.
Approx Net Weight	: 8.2 kg.	8.4 kg.



HEAVY DUTY DRILL MODEL NO : WD2C | WD3C

	WD2C	WD3C
Capacity	: 6 mm	10 mm
Watts Input (full Load)	: 475 Watts	550 Watts
No Load Speed	: 2400 r.p.m	1000 r.p.m
Approx Net Weight	: 3.2 kg.	3.6 kg.



HEAVY DUTY DRILL MODEL NO : WD34C

Capacity	:	13 mm
Watts Input (full Load)	:	500 Watts
No Load Speed	:	550 r.p.m.
Approx Net Weight	:	3.9 kg.



HEAVY DUTY DRILL MODEL NO : NW8 | NW10

	NW8	NW10
Capacity	: 25 mm	31 mm
Watts Input (full Load)	: 660 Watts	850 Watts
No Load Speed	: 380 r.p.m.	280 r.p.m.
Approx Net Weight	: 9.9 kg.	10 kg.



HEAVY DUTY DRILL MODEL NO : 14130 | 14230

	14130	14230
Capacity	: 13 mm	13 mm
Watts Input (full Load)	: 750 Watts	750 Watts
No Load Speed	: 750 r.p.m.	750 r.p.m.
Approx Net Weight	: 4.4 kg.	4.4 kg.



LIGHT DUTY DRILL MODEL NO : SD4C

Model	:	SD4C
Capacity	:	13 mm
Watts Input (full Load)	:	435 Watts
No Load Speed	:	700 r.p.m.
Approx Net Weight	:	4.4 kg.
Body	:	Universally accepted general drill Two way holding Al-die cast



LIGHT DUTY DRILL MODEL NO : EJ3C

Model	:	EJ3C
Capacity	:	10 mm
Watts Input (full Load)	:	235 Watts
No Load Speed	:	700 r.p.m.
Approx Net Weight	:	2.4 kg.
Body	:	Low speed Masonary work Multi functional Al-die cast body



LIGHT DUTY DRILL MODEL NO : EG2C

Model	:	EG2C
Capacity	:	6 mm
Watts Input (full Load)	:	235 Watts
No Load Speed	:	2800 r.p.m.
Approx Net Weight	:	1.9 kg.
Body	:	Unique grip Multi-functional Al-die cast



GRINDER MODEL NO : AG7 | AG9

	AG7	AG9
Rated Power	: 2200 watts	2200 watts
Wheel Size	: 180x22x6mm	230x22x6mm
Speed	: 7000 r.p.m.	5600 r.p.m.
Net Weight	: 9.5 Kg	9.5 Kg



STRAIGHT GRINDER MODEL NO : GQ4 BR

	GQ4 BR	GQ6
Rated Power	: 775 watts	1200 watts
Wheel Size	: 100x20x12.7mm	150x25x15.9mm
Speed	: 5000 r.p.m	5600 r.p.m
Net Weight	: 5.6 kg	9.2 kg

STRAIGHT GRINDER
MODEL NO : 36100



Rated Power	:	1000 watts
Wheel Size	:	100x20x12.7mm
Speed	:	5800 r.p.m
Net Weight	:	5.1 kg

GRINDER
MODEL NO : HSG | HSG BR



	HSG	HSG BR
Rated Power	:	300 watts
Capacity	:	6mm (collet)
Speed	:	16000 r.p.m
Net Weight	:	1.9 kg
		500 watts
		6mm (collet)
		20000 r.p.m
		1.9 kg

BENCH GRINDER
MODEL NO : TG6 1PH | TG6 3PH



	TG6 (1ph)	TG6 (3ph)
Rated Power	:	265 watts
Wheel Size	:	150x16x12.7mm
Speed	:	2950 r.p.m
Net Weight	:	12.2 kg
		285 watts
		150x16x12.7mm
		2950 r.p.m
		12 kg

LATHE GRINDER
MODEL NO : GL3



Rated Power	:	400 watts
Wheel Size	:	75x13x19mm
Speed	:	8000 r.p.m (Ext)
		19000 r.p.m (Int)
Net Weight	:	9.8 kg

METAL FLEXIBLE SHAFT

MODEL NO : FF2



Rated Power	:	370 watts
Capacity	:	6mm (collect)
Speed	:	1200/11500 r.p.m
Net Weight	:	5.4 kg

MODEL NO : FSG2



Rated Power	:	370 watts
Capacity	:	6mm (collect)
Speed	:	12800 r.p.m
Net Weight	:	4.9 kg

METAL BLOWER

TWO SPEED AIR BLOWER
MODEL NO : 77750



Capacity	:	2.0m³/min /1.6m³/min
Watts Input (full Load)	:	750 Watts, 450 Watts
Air Velocity	:	400 kmph, 315 kmph
Approx Net Weight	:	3.4kg.
Rated Voltage	:	235V AC

SINGLE SPEED AIR BLOWER
MODEL NO : NWB



Capacity	:	1.5m³/min
Watts Input (full Load)	:	350 Watts
Air Velocity	:	308 kmph
Approx Net Weight	:	4.5kg
Rated Voltage	:	235V AC

INDUSTRIAL TOOLS

HORIZONTAL SANDER
MODEL NO : HS7 AR | HS7 BR



	HS7 AR	HS7 BR
Rated Power	:	600 watts
Capacity	:	180mm
Speed	:	4200 r.p.m
Net Weight	:	5.2 kg
		1000 watts
		180mm
		5200 r.p.m
		5.7 kg

VERTICAL SANDER
MODEL NO : VSM



Rated Power	:	500 watts
Capacity	:	180mm
Speed	:	2200 r.p.m
Net Weight	:	5.4 kg

SANDER
MODEL NO : 25180



Rated Power	:	1000 watts
Capacity	:	180mm
Speed	:	5200 r.p.m
Net Weight	:	5 kg

PORTABLE TAPPING MACHINE
MODEL NO : TP8



Rated Power	:	450 watts
Capacity	:	3mm-10mm
Speed	:	550 r.p.m
Net Weight	:	3.9 kg

WATER PUMPSET



MODEL NO : RP-30

Engine	:	2-Stroke
Rated Power	:	6.5 Hp
Suction Diameter	:	76mm
Discharge Diameter	:	76mm
Height (m)	:	28m
Suction Head (m)	:	7m



"It does not matter how slowly you go as long as you do not stop."

BRUSH CUTTER



MODEL NO : RBC 2S (SP)

Engine	:	2 Stroke
Rated Power	:	1.45 kw
Speed	:	6500 r.p.m
Displacement	:	51.7 CC



MODEL NO : RBC 4S (SP)

Engine	:	4 Stroke
Rated Power	:	0.85 kw
Speed	:	6500 r.p.m
Displacement	:	35.8 cc



MODEL NO : RBC 4S (BP)

Engine	:	4 Stroke
Rated Power	:	0.85 kw
Speed	:	6500 r.p.m
Displacement	:	35.8 cc



"Safety is gainful, Accident is painful."

CHAIN SAW



MODEL NO : RS- 63

63CC Engine

Engine	:	2-Stroke Petrol Driven, Air Cooled
Cylinder	:	Single Cylinder
Rated Power	:	2.9kw/8500r/min
Speed	:	11000 ±1000r/min
Chain Sizes	:	18" / 20" / 22" / 24"
Net. Weight	:	7.8 kg



EARTH AUGER



MODEL NO : ED520

Operator : Single Man

Engine	:	44F-5 2 Stroke
Speed	:	6500 r.p.m.
Rated Power	:	1.45KW
Displacement	:	52CC



MODEL NO : ED630

Operator : Double Man

Engine	:	48F 2 Stroke
Speed	:	6500 r.p.m.
Rated Power	:	2.2KW
Displacement	:	63CC

FOGGING MACHINE



MODEL NO : RF-01 MINI

Tank	:	2 Ltr
Fuel	:	Butane Gas
Fogging Particle	:	5-30 Microns
Net. Weight (Dry)	:	1.4 Kg



MODEL NO : RF-02 AUTO

Chemical Tank	:	6 Itr. (S.S)
Fuel Tank	:	1.2 Itr. (S.S)
Fogging Particle	:	10 – 60 Microns
Fuel Consumption	:	1.5 ltr/hr
Diesel Consumption	:	25 ltr/hr
Net. Weight (Dry)	:	9 kg

METAL DRILL



REVERSIBLE DRILL MODEL NO : RAD-302

Drilling Cap	:	3/8"
Speed	:	1800 r.p.m
Air Inlet	:	1/4"
Air Hose	:	3/8"
Air Consumption	:	6 cfm
Net. Weight	:	1.1 kg



REVERSIBLE DRILL MODEL NO : RAD-402

Drilling Cap	:	1/2"
Speed	:	800 r.p.m
Air Inlet	:	1/4"
Air Hose	:	3/8"
Air Consumption	:	8 cfm
Net. Weight	:	1.6 kg



PNEUMATIC DRILL MODEL NO : RAD-06

NEW

Drilling Cap	:	1/4" or 6mm
Speed	:	4000 r.p.m
Air Inlet	:	3/8"
Noise	:	93dB
Air Consumption	:	2.7 cfm @90psi
Net. Weight	:	0.89 kg



"No job is so urgent that we can't take the time to do it safely."

GRINDER



AIR MICRO DIE GRINDER MODEL NO : DG-56

Speed	:	56000 r.p.m
Air Inlet	:	1/4"
Air Hose	:	5mm
Air Consumption	:	7 cfm
Net. Weight	:	0.21 kg



AIR DIE GRINDER MODEL NO : PG-1101H

Speed	:	28000 r.p.m
Air Inlet	:	6.3mm
Air Hose	:	5mm
Air Consumption	:	3.5 cfm
Net. Weight	:	0.37 kg



AIR DIE GRINDER (INDUSTRIAL) MODEL NO : DG 6-35

Speed	:	35000 r.p.m
Air Inlet	:	1/4" NPT
Length	:	165mm
Air Consumption	:	10 cfm
Net. Weight	:	0.45kg



5" EXTENDED DIE GRINDER MODEL NO : EDG-GR2205

Speed	:	22000 r.p.m
Air Inlet	:	1/4" NPT
Length	:	280mm
Air Consumption	:	3.1 cfm
Net. Weight	:	0.80kg



GRINDER MODEL NO : DG L-21

Speed	:	21000 r.p.m
Air Inlet	:	3/8" NPT
Length	:	315mm
Air Consumption	:	27 cfm
Net. Weight	:	2.80kg



90° ANGLE GRINDER MODEL NO : ADG-1106H

Speed	:	20000 r.p.m
Air Inlet	:	1/4" NPT
Length	:	100mm
Air Consumption	:	3.5 cfm
Net. Weight	:	2.49kg



4" AIR ANGLE GRINDER MODEL NO : AG-406

Speed	:	11000 r.p.m
Air Inlet	:	1/4" NPT
Length	:	242mm
Air Consumption	:	6 cfm
Net. Weight	:	1.82kg



7" AIR ANGLE GRINDER MODEL NO : AG-GR706

Speed	:	7000 r.p.m
Air Inlet	:	3/8" NPT
Spindle	:	M14
Air Consumption	:	9 cfm
Net. Weight	:	3.18kg



PNEUMATIC STRAIGHT GRINDER MODEL NO : SG 150

Capacity	:	150mm x 25mm
Speed	:	6000 r.p.m
Air Inlet	:	1/2" BSP
Air Consumption	:	56 cfm
Net. Weight	:	5.5 kg



"Out of difficulties grow miracles."

IMPACT WRENCH



IMPACT WRENCH KIT
MODEL NO : IW-1700K-A

Bolt Capacity	:	5/8"
Speed	:	7500 r.p.m
Air Inlet	:	1/4"
Air Consumption	:	5.4 cfm
Net. Weight	:	2.4 kg



COMPOSITE IMPACT WRENCH
MODEL NO : IW-1930T

Bolt Capacity	:	19mm
Speed	:	9000 r.p.m
Air Inlet	:	1/4"
Air Consumption	:	5.4 cfm
Net. Weight	:	2.2 kg



COMPOSITE IMPACT WRENCH
MODEL NO : IW-1281

Bolt Capacity	:	5/8" (16mm)
Speed	:	10000 r.p.m
Air Inlet	:	1/4"
Air Consumption	:	5.4 cfm
Net. Weight	:	2.2 kg



AIR RATCHET WRENCH
MODEL NO : RW-RA12A

Length	:	254mm
Speed	:	160 r.p.m
Air Inlet	:	1/4"
Air Consumption	:	3.7 cfm
Net. Weight	:	1.20 kg

SANDER



DUST FREE ORBITAL SANDER
MODEL NO : OS-303

Pad Size	:	5" Velcro Type
Speed	:	10000 r.p.m
Air Inlet	:	1/4"
Air Consumption	:	2 cfm
Net. Weight	:	0.9 kg



DUST FREE ORBITAL SANDER
MODEL NO : OS-306

Pad Size	:	6" Velcro Type
Speed	:	11000 r.p.m
Air Inlet	:	1/4"
Air Consumption	:	4.75 cfm
Net. Weight	:	0.9 kg



AIR BELT SANDER
MODEL NO : BS 385

Length (mm)	:	415*118*82
Speed	:	13000 r.p.m
Air Inlet	:	1/4"
Air Consumption	:	4.5 cfm
Net. Weight	:	1.5 kg



*"The best preparation
for tomorrow is doing
your best today."*

SAND RAMMER



MODEL NO : BSR 1

Blow/min	:	8500
Length	:	530mm
Air Inlet	:	3/8" NPT
Air Consumption	:	25 cfm
Net. Weight	:	5.7 kg



MODEL NO : FSR 1

Blow/min	:	800
Length	:	1258mm
Air Inlet	:	A 1/2" BSP
Air Consumption	:	25 cfm
Net. Weight	:	11 kg

"The best way to ensure our brand safety is by keeping everyone who is part of it safe."



UTILITY TOOLS



AIR SCREW DRIVER
MODEL NO : SD-5MA

Capacity	:	6-7mm
Speed	:	9000 r.p.m
Torque	:	25-30 N.M
Air Consumption	:	2 cfm
Net. Weight	:	0.83 kg



CHIPPING HAMMER
MODEL NO : CH 3

Blow/min	:	2100 BPM
Lenght	:	76.2mm (3")
Air Inlet	:	3/8" BSP
Net. Weight	:	7 kg



AIR HYDRAULIC RIVETER
MODEL NO : HR-RV105L

Traction Power	:	1.22 kg
Capacity	:	2.4/3.2/4/4.8m blind rivets
Stoke	:	18mm
Air Pressure	:	90 PSI
Net. Weight	:	1.5 kg



PNEUMATIC WELD FLUX CHIPPER
MODEL NO : WFC 42

Capacity	:	150 mm x 25 mm
Free Speed	:	6000 r.p.m.
Air Inlet	:	1/2" bsp
Air Consumption	:	56 cfm
Net. Weight	:	5.5 kg

CONCRETE BREAKER



MODEL NO : CB 117

Length	:	740mm
Piston Dia	:	57mm
Air Inlet	:	19mm
Shank Size	:	32x160mm
Net. Weight	:	37kg



MODEL NO : CB 1210

Length	:	540mm
Piston Dia	:	48mm
Air Inlet	:	19mm
Shank Size	:	25x108mm
Net. Weight	:	22kg

METAL GRINDER



AIR DIE GRINDER
MODEL NO : PG-144

Collect Size	:	1/4"
Speed	:	28000 r.p.m
Air Inlet	:	6.3mm
Air Consumption	:	3.5 cfm
Net. Weight	:	0.37 kg



5" AIR ANGLE GRINDER
MODEL NO : AG-449

Disc Size	:	125mm (5 inch)
Speed	:	11000 r.p.m
Exhaust	:	Front
Air Consumption	:	4.48 cfm/126.87L/min
Minimum Hose Size	:	3/8" (10mm)

METAL IMPACT WRENCH



IMPACT WRENCH
MODEL NO : IW-760

Bolt Capacity	:	16mm
Speed	:	7000 r.p.m
Torque	:	380mm
Air Consumption	:	4.16 cfm
Net. Weight	:	2.12 kg



AIR IMPACT WRENCH
MODEL NO : IW-1050

Bolt Capacity	:	50mm
Speed	:	3800 r.p.m
Torque	:	3200 N/m
Anvil	:	8" Long
Net. Weight	:	16.7 kg



ARC SERIES



MODEL NO : ECO-200 N

Input Supply	: AC 220v ±15%, 1 ph 50Hz
Power (KVA)	: 6
Output Current Range (A)	: 20 - 200
Duty Cycle (%)	: 60%
Inverter Technology	: IGBT
Net. Weight	: 6 kg



MODEL NO : WA20

Input Supply	: AC 220v ±15%, 1 ph 50Hz
Power (KVA)	: 8.2
Output Current Range (A)	: 30-200
Duty Cycle (%)	: 60%
Inverter Technology	: IGBT
Net. Weight	: 6.5 kg



MODEL NO : RA20

Input Supply	: AC 220v ±15%, 1 ph 50Hz
Power (KVA)	: 9.59
Output Current Range (A)	: 30-200
Duty Cycle (%)	: 60%
Inverter Technology	: MOSFET
Net. Weight	: 8 kg



MODEL NO : MA20

Input Supply	: AC 220v ±15%, 1 ph 60Hz
Power (KVA)	: 6
Output Current Range (A)	: 20-200
Duty Cycle (%)	: 60%
Inverter Technology	: MOSFET
Net. Weight	: 8 kg



MODEL NO : R76

Input Supply	: AC 220v ±15%, 1 ph 50Hz
Power (KVA)	: 10.1
Output Current Range (A)	: 30-200
Duty Cycle (%)	: 60%
Inverter Technology	: IGBT
Net. Weight	: 8.2 kg



MODEL NO : RW20A

Input Supply	: AC 220v ±15%, 1 ph 50Hz
Power (KVA)	: 6
Output Current Range (A)	: 30-200
Duty Cycle (%)	: 60%
Inverter Technology	: IGBT
Net. Weight	: 4 kg



MODEL NO : ECO-250

Input Supply	: AC 230v ±15%, 1 ph 50Hz
Power (KVA)	: 8.3
Output Current Range (A)	: 20-250
Duty Cycle (%)	: 60%
Inverter Technology	: IGBT
Net. Weight	: 7 kg



MODEL NO : RA25 S

Input Supply	: AC 230v ±15%, 1 ph 50Hz
Power (KVA)	: 9.4
Output Current Range (A)	: 30-250
Duty Cycle (%)	: 60%
Inverter Technology	: MOSFET
Net. Weight	: 17.5 kg



MODEL NO : RA25

Input Supply	: AC 415v ±15%, 3 ph 50Hz
Power (KVA)	: 9.4
Output Current Range (A)	: 30-250
Duty Cycle (%)	: 60%
Inverter Technology	: MOSFET
Net. Weight	: 17.5 kg



MODEL NO : RA25D

Input Supply	: 230V / 1Ph, 415V / 2Ph, 50Hz
Power (KVA)	: 6 KVA - 1 Ph / 7.5 KVA - 2 Ph
Output Current Range (A)	: 20-250A
Duty Cycle (%)	: 60%
Inverter Technology	: IGBT
Net. Weight	: 4.5 kg



MODEL NO : RA30D

Input Supply	: 230V 1Ph / 415V 2Ph, 50Hz
Power (KVA)	: 8.5 KVA - 1 Ph / 6.2 KVA - 2 Ph
Output Current Range (A)	: 20-315
Duty Cycle (%)	: 60%
Inverter Technology	: IGBT
Net. Weight	: 8.5 kg



MODEL NO : RA30-1 & 2

Input Supply	: AC 230v ±15%, 1 ph 50Hz
Power (KVA)	: 13/6
Output Current Range (A)	: 20-300
Duty Cycle (%)	: 60%
Inverter Technology	: IGBT
Net. Weight	: 7.5 kg

ARC SERIES



MODEL NO : RA40HD

Input Supply	: AC 415v ±15%, 50Hz
Power (KVA)	: 13
Output Current Range (A)	: 30 – 400
Duty Cycle (%)	: 60%
Inverter Technology	: IGBT
Net. Weight	: 22 kg



MODEL NO : RA40GT

Input Supply	: 230V 1Ph / 415V, 2Ph & 3Ph
Power (KVA)	: 8.5 KVA – 1 Ph / 6.2 KVA – 2 Ph / 14 KVA – 3 Ph
Output Current Range (A)	: 30-400
Duty Cycle (%)	: 60%
Insulation Grade	: F
Net. Weight	: 10 kg



MODEL NO : RA40

Input Supply	: AC 415v ±15%, 3 Ph 50Hz
Power (KVA)	: 18.2
Output Current Range (A)	: 30-400
Duty Cycle (%)	: 60%
Inverter Technology	: IGBT
Net. Weight	: 26 kg



MODEL NO : RA40H

Input Supply	: AC 415v ±15%, 3 Ph 50Hz
Power (KVA)	: 16.8
Output Current Range (A)	: 40-400
Duty Cycle (%)	: 60%
Inverter Technology	: IGBT
Net. Weight	: 18 kg



MODEL NO : RA40HD+

Input Supply	: AC415V ±15%, 3Ph 50Hz
Power (KVA)	: 18
Output Current Range (A)	: 20-400
Duty Cycle (%)	: 60%
Power Factor	: 0.93
Net. Weight	: 27 kg



MODEL NO : RA40HI

Input Supply	: AC415V ±15%, 3Ph 50Hz
Power (KVA)	: 13
Output Current Range (A)	: 20-320
Duty Cycle (%)	: 60%
Insulation Grade	: F
Net. Weight	: 18 kg



MODEL NO : RA40HK

Input Supply	: AC 415v ±15%, 3Ph 60Hz
Power (KVA)	: 11
Output Current Range (A)	: 20-400
Duty Cycle (60%)	: 300A
Inverter Technology	: IGBT
Net. Weight	: 12.5 kg



MODEL NO : RA60N

Input Supply	: AC 415v ±15%, 3 Ph 60Hz
Power (KVA)	: 30
Output Current Range (A)	: 20-600
Duty Cycle (%)	: 60%
Insulation Grade	: H
Net. Weight	: 35 kg



MODEL NO : RA50

Input Supply	: AC 415v ±15%, 3Ph 60Hz
Power (KVA)	: 25.3
Output Current Range (A)	: 40-500
Inverter Technology	: IGBT
Insulation Grade	: F
Net. Weight	: 40 kg



MODEL NO : RA63

Input Supply	: AC 415v ±15%, 3Ph 60Hz
Power (KVA)	: 32
Output Current Range (A)	: 30-630
Duty Cycle (%)	: 60%
Inverter Technology	: IGBT
Net. Weight	: 54 kg



TIG SERIES



MODEL NO : RT20

Input Supply	: AC 220v ±15%, 50Hz
Power (KVA)	: 9.59
Output Current Range (A)	: 10 – 200
Duty Cycle (%)	: 60%
Inverter Technology	: MOSFET
Net. Weight	: 8 kg



MODEL NO : RT20P

Input Supply	: AC 220v ±15%, 50Hz
Power (KVA)	: 6.2/9.59
Output Current Range (A)	: 5–200
Pulse Mode	: Yes
Duty Cycle (%)	: 60%
Inverter Technology	: MOSFET
Net. Weight	: 8 kg



MODEL NO : RT20 A

Input Supply	: AC 220v ±15%, 50Hz
Power (KVA)	: 9.59
Output Current Range (A)	: 5–200
Output Current	: AC & DC both
Duty Cycle (%)	: 60%
Inverter Technology	: MOSFET
Net. Weight	: 22.1 kg



MODEL NO : RT25

Input Supply	: AC 415v ±15%, 50Hz
Power (KVA)	: 9.5
Output Current Range (A)	: 10–250
Duty Cycle (%)	: 60%
Inverter Technology	: MOSFET
Net. Weight	: 17.5 kg



MODEL NO : RT31PA

Input Supply	: AC 415v ±15%, 50Hz
Power (KVA)	: 12.9
Output Current Range (A)	: 5–315
Output current	: AC & DC both
Pulse Mode	: Yes
Duty Cycle (%)	: 60%
Inverter Technology	: MOSFET
Net. Weight	: 34 kg



MODEL NO : RT63

Input Supply	: AC 415v ±15%, 3 Ph, 50Hz
Power (KVA)	: 38.16
Output Current Range (A)	: 30–630
Duty Cycle (%)	: 60%
Inverter Technology	: IGBT
Net. Weight	: 54 kg



MODEL NO : RT50

Input Supply	: AC 415v ±15%, 50Hz
Power (KVA)	: 25.2
Output Current Range (A)	: 10–500
Duty Cycle (%)	: 60%
Inverter Technology	: IGBT
Net. Weight	: 42 kg



"your greatest asset is your earning ability. your greatest resource is your time"

MIG SERIES



MODEL NO : RM20

Input Supply	: AC 220v ±15%, 1Ph 50Hz
Power (KVA)	: 8.2
Output Current Range (A)	: 50–200
Duty Cycle (%)	: 60%
Wire Feeder	: In-Built
Inverter Technology	: IGBT
MIG Wire (mm)	: 0.8
Net. Weight	: 30 kg



MODEL NO : RM25

Input Supply	: AC 415v ±15%, 3Ph 50Hz
Power (KVA)	: 8.4
Output Current Range (A)	: 50–250
Duty Cycle (%)	: 60%
Inverter Technology	: IGBT
MIG Wire (mm)	: 0.8mm
Net. Weight	: 25.5 kg



MODEL NO : RM40 N

Input Supply	: AC 415v ±15%, 3Ph, 50Hz
Power (KVA)	: 15
Output Current Range (A)	: 50–400
Duty Cycle (%)	: 60%
Inverter Technology	: IGBT
MIG Wire (mm)	: 0.8/1.2mm
Net. Weight	: 35.5 kg



MODEL NO : RM50

Input Supply	: AC 415v ±15%, 3Ph 60Hz
Power (KVA)	: 25.3
Output Current Range (A)	: 80–500
Duty Cycle (%)	: 60%
Inverter Technology	: IGBT
MIG Wire (mm)	: 0.8/1.2/1.6mm
Net. Weight	: 49.5 kg

MIG SERIES



MODEL NO : RM 50P

NEW

Input Supply	: 415V ± 10%, 3Ph 50Hz
Power (kVA)	: 27.6
Output Current Range (A)	: 20 – 500
Duty Cycle (%)	: 60%
Pulse Mode	: Yes
Inverter Technology	: IGBT
MIG Wire (mm)	: 0.8/1.2/1.6mm
Net. Weight	: 67.5 kg



MODEL NO : RM63

Input Supply	: AC 415v ±15%, 3Ph 60Hz
Output Current Range (A)	: 80–630
Duty Cycle (%)	: 60%
Inverter Technology	: IGBT
MIG Wire (mm)	: 0.8/1.2/1.6mm
Net. Weight	: 49.5 kg

MODEL NO : RM63

Input Supply	: AC 415± 15%, 3Ph
Power (kVA)	: 36.2
Output Current Range (A)	: 80–630
Duty Cycle (%)	: 60%
Inverter Technology	: IGBT
MIG Wire (mm)	: 0.8/1.2/1.6mm
Net. Weight	: 49.5 kg



"Always desire to learn something useful"

AIR PLASMA CUTTER



MODEL NO : RC80

Input Supply (V)	: AC 415 ±15%,3Ph, 50Hz
Power (kVA)	: 15
Rated Input Current (A)	: 20
Output Current Range (A)	: 20-80
Technology Required Air	: IGBT
Cutting Thickness (mm)	: 1-15
MMA Facility	: Available (250amp)
Net. Weight	: 25 kg



MODEL NO : RC10

Input Supply (V)	: AC 415 ±15%,3Ph, 50Hz
Power (kVA)	: 15.5
Rated Input Current (A)	: 21
Output Current Range (A)	: 20-100
Technology Required Air	: IGBT
Cutting Thickness (mm)	: 1-30
MMA Facility	: Available (400amp)
Net. Weight	: 26.5 kg

MODEL NO : RC16

Input Supply (V)	: AC 415 ±15%,3Ph, 50Hz
Power (kVA)	: 29
Rated Input Current (A)	: 40
Output Current Range (A)	: 20-160
Technology Required Air	: IGBT
Cutting Thickness (mm)	: 1-50
MMA Facility	: NA
Net. Weight	: 60 kg



"If opportunity doesn't knock, build a door."

SUB MERGED ARC WELDER



MODEL NO : RS100

Input Supply	: AC 415 ±15%, 50Hz
Power (kVA)	: 52
Rated Input Current (A)	: 72.3A
Output Current Range (A)	: 100-1000A
Power Factor	: 0.93
OCV (V)	: 79
Net. Weight	: 85 kg



MODEL NO : RS125

Input Supply	: AC 415 ±15%, 50Hz
Power (kVA)	: 64.5
Rated Input Current (A)	: 90A
Output Current Range (A)	: 100-1250A
Power Factor	: 0.93
OCV (V)	: 80
Net. Weight	: 98 kg

FCT SERIES



MODEL NO : FCT400

Input Supply	: AC 380/415/440V 2Lines of 3Ph
Power (kVA)	: 23
Rated Input Current (A)	: 55
Output Current Range (A)	: 75-400
Cooling	: Forced Air
OCV (V)	: 78
Net. Weight	: 85 kg



MODEL NO : FCT600

Input Supply	: AC 380/415/440V 2Lines of 3Ph
Power (kVA)	: 39
Rated Input Current (A)	: 94
Output Current Range (A)	: 60-600
Cooling	: Forced Air
OCV (V)	: 80
Net. Weight	: 150 kg

THYRISTORISED RECTIFIER



MODEL NO : RT400

Input Supply (v)	: AC 415 ±15%, 50Hz
Rated Power (KVA)	: 21.5
Output Current Range (A)	: 10-400
OCV (V)	: 95
Insulation Class	: H
Net. Weight	: 112 kg



MODEL NO : RT60

Input Supply (v)	: AC 415v ±15%, 3 ph 50Hz
Rated Power (KVA)	: 39
Output Current Range (A)	: 10-600
OCV (V)	: 95
Insulation Class	: H
Net. Weight	: 145 kg

DIESEL ENGINE DRIVEN WELDING GENERATOR



MODEL NO : RWG350

Engine/HP	: ESCORTS-KUBOTA/40
Fuel Type	: HSD
Welding Current Range (A)	: 30-350
Cylinder	: 3
Cooling	: Coolant Cooled
Dimension (mm)	: 3100 x 1600 x 3200
Net. Weight	: 1100 kg



MODEL NO : RWG400 3C

Engine/HP	: ESCORTS-KUBOTA/57
Fuel Type	: HSD
Welding Current Range (A)	: 30-400
Cylinder	: 3
Cooling	: Coolant Cooled
Dimension (mm)	: 3500 x 1675 x 3200
Net. Weight	: 1300 kg



MODEL NO : RWG500

Engine/HP	: ESCORTS-KUBOTA/57
Fuel Type	: HSD
Welding Current Range (A)	: 40-500
Cylinder	: 3
Cooling	: Coolant Cooled
Dimension (mm)	: 3500 x 1675 x 3200
Net. Weight	: 1300 kg



"A champion is someone who gets up when he can't."

STUD WELDING MACHINE



MODEL NO : CD 208

TYPE : CAPACITOR DISCHARGE

Input Voltage	: 230V ±15%, 1Ph, 50Hz
Stud Diameter	: 3-8mm
Charging Capacity	: 75,000 pF
Welding Time	: 0.001-0.003Sec
Net. Weight	: 19 kg



MODEL NO : RDA1600

TYPE : DRAWN ARC

Input Voltage	: AC 415 ±15%, 3Ph 50Hz
Power (KVA)	: 85/80
Rated Input Current (A)	: 124 Amps
Weldable Stud Diameter (mm)	: 6-16mm
Welding Time (sec.)	: 0.01-9.99
Insulation Grade	: F
Weight (Kg)	: 90Kg



MODEL NO : RDA2500

TYPE : DRAWN ARC

Input Voltage	: AC 415 ±15%, 3Ph 50Hz
Power (KVA)	: 99/94
Rated Input Current (A)	: 162 Amps
Weldable Stud Diameter (mm)	: 6-25mm
Welding Time (sec.)	: 0.01-9.99
Insulation Grade	: F
Weight (Kg)	: 97Kg



MODEL NO : RDA3100

TYPE : DRAWN ARC

Input Voltage	: AC 415 ±15%, 3Ph 50Hz
Power (KVA)	: 137/130
Rated Input Current (A)	: 220 Amps
Weldable Stud Diameter (mm)	: 6-31mm
Welding Time (sec.)	: 0.01-9.99
Insulation Grade	: F
Weight (Kg)	: 100Kg

BENCH TYPE PLASMA CUTTING MACHINE



MODEL NO : RWB 1503 | RWB 1506

	RWB 1503	RWB 1506
Track Width (mm) :	1500mm	1500mm
Track Length(mm) :	3000mm	6000mm
<i>(One Flame & One Plasma)</i>		



"It is during our darkest moments that we must focus to see the light."

CNC FLAME / PLASMA CUTTING MACHINE



MODEL NO : RWCUT 2500

Track Width (mm)	:	2500
Track Length (mm)	:	6000
Solenoid Valve	:	Airtac
Gear Box Type	:	Planetary Type
Controller	:	FLSK 2300B
Software	:	Fastcam (Australia)
Rack & Pinion	:	Helical 20x20 mm



MODEL NO : RWCUT 3500

Track Width (mm)	:	3500
Track Length (mm)	:	6000
Solenoid Valve	:	Airtac
Gear Box Type	:	Planetary Type
Controller	:	FLSK 2300B
Software	:	Fastcam (Australia)
Rack & Pinion	:	Helical 20x20 mm



MODEL NO : RWCUT 4000

Track Width (mm)	:	4000
Track Length (mm)	:	8000
Solenoid Valve	:	Airtac
Gear Box Type	:	Planetary Type
Controller	:	FLSK 2300B
Software	:	Fastcam (Australia)
Rack & Pinion	:	Helical 20x20 mm



MODEL NO : RCN 1500P

Input Power	:	220V, 1Ph, 50Hz
Type	:	Cantilever
Speed	:	3000 mm/min.
Rated Power	:	1Ph. / 230V 50 Hz
Language	:	English
Program Input	:	USB Stick
Torch	:	≤90mm
Accuracy	:	±0.2mm/m

LASER CUTTING MACHINE



LASER CUTTING MACHINE (SHEET AND TUBE)

Laser Type	:	Fiber Laser Source IPG / Raycus/ Max
Laser wave length	:	1070-1080nm
XYZ axis working length	:	3000mm/1500mm/120mm
Cutting thickness	:	0.5-16mm (Depend on materials)
Traverse Speed	:	100M/min
Maximum acceleration	:	1G
Net Weight	:	5500 kg



If we did all the things we are capable of, we would literally astound ourselves.

LASER WELDING MACHINE



LASER WELDING MACHINE


Laser Power	:	1Kw/1.5 Kw/2 Kw /3Kw
Beam Width	:	0.2 to 5mm (Depending on Welding Head)
Laser Wavelength	:	1070 nm
Optical Fiber	:	100um, 5m
Head Type	:	Wobble with Galvo Technology
Continuous Working Time	:	24 Hours
Power Supply Demand	:	230V 1Ph, 50Hz



LASER MARKING MACHINE

Layer Power	:	20/30/50/100W
Input Supply	:	220V AC 50Hz
Laser Wave (length)	:	1074nm
Max Scanning Speed	:	≤8000mm/s

FIBER LASER CUTTING MACHINE



FIBER LASER CUTTING MACHINE (OPEN TYPE)

Laser Type	:	Fiber Laser Source IPG / Raycus/ Max
Laser wave length	:	1070-1080nm
XYZ axis working length	:	3000mm/1500mm/120mm
Cutting thickness	:	0.5-16mm (Depend on materials)
Traverse Speed	:	120M/min
Maximum acceleration	:	1.5G
Net Weight	:	4000 kg



FIBER LASER CUTTING MACHINE (EXCHANGE TABLE TYPE)

Laser Type	:	Fiber Laser Source IPG / Raycus/ Max
Laser wave length	:	1070-1080nm
XYZ axis working length	:	3000mm/1500mm/120mm
Cutting thickness	:	0.5-16mm (Depend on materials)
Traverse Speed	:	120M/min
Maximum acceleration	:	1.5G
Net Weight	:	7000 kg

WATER COOLING UNIT



MODEL NO : RWCU-N

Input Supply	:	230V, 1Ph, 50Hz
Tank Capacity	:	65 ltrs
Size	:	28" x 16" x 18"
Cooling	:	Fan
Radiator Size	:	15"
Meter type	:	Digital



MODEL NO : RPC- 1

Input Supply	:	230V, 1Ph 50Hz
Cutting Area	:	25 – 750 mm diameter (approx.)
Speed	:	100 – 650mm / min (approx.)
Motor	:	Series Fraction Horse Power, 220V
Cutter Movement	:	Pinion Knob



MODEL NO : SPM 6

	No Load	Full Load
Rated Voltage	: 235V AC/DC	235V AC/DC
Input - watts	: 2.8W	5.5W
Speed - r.p.m.	: 625	1200
Drive Roll Dia	: 14000	9600



MODEL NO : SPM 8

	No Load	Full Load
Rated Voltage	: 220V AC/DC	220V AC/DC
Input - watts	: 1.2W	2.2W
Speed - r.p.m.	: 254	450
Drive Roll Dia	: 4000	2800
Wire feeder speed	: -	1



MODEL NO : SPM 18

	No Load	Full Load
Rated Voltage	: 220V AC/DC	220V AC/DC
Current - amps	: 1.1	2.8
Input - watts	: 230W	580W
Speed - r.p.m.	: 15000	9200
Rating - Minutes	: -	10



MODEL NO : SPM 23

	No Load	Full Load
Rated Voltage	: 220V AC/DC	220V AC/DC
Current - amps	: 0.58	1.2
Input - watts	: 124W	230W
Speed - r.p.m.	: 18000	9000
Rating - Minutes	: -	1



MODEL NO : SPM 24

	No Load	Full Load
Rated Voltage	: 235V AC/DC	235V AC/DC
Current - amps	: 0.6	1.15
Input - watts	: 130W	235W
Speed - r.p.m.	: 2800	1500
Rating - Minutes	: -	30



MODEL NO : SPM 25

	No Load	Full Load
Rated Voltage	: 220V AC/DC	220V AC/DC
Current - amps	: 0.75	3.0
Input - watts	: 156W	550W
Speed - r.p.m.	: 15000	5500
Rating - Minutes	: -	1



MODEL NO : SPM 25G

	No Load	Full Load
Rated Voltage	: 110V AC/DC	110V AC/DC
Current - amps	: 1.5	7
Input - watts	: 175W	650W
Speed - r.p.m.	: 200	120
Rating - Minutes	: -	-



MODEL NO : SPM 35

	No Load	Full Load
Rated Voltage	: 24F/36A V DC	24F/36A V DC
Current - amps	: 1.2	5
Input - watts	: 43.2W	180W
Speed - r.p.m.	: 5000	4600
Rating - Minutes	: -	Continuous



MODEL NO : SPM 43

	No Load	Full Load
Rated Voltage	: 240V AC/DC	240V AC/DC
Current - amps	: 1.20	4.5
Input - watts	: 280W	970W
Speed - r.p.m.	: 16000	8000
Rating - Minutes	: -	5



MODEL NO : SPM 58 / 59

	No Load	Full Load
Rated Voltage	: 90V DC	90V DC
Current - amps	: 0.5	1
Input - watts	: 45W	90W
Speed - r.p.m.	: 40	38
Rating - Minutes	: -	Continuous



MODEL NO : SPM 63

	No Load	Full Load
Rated Voltage	: 220V DC	220V DC
Current - amps	: 0.42	0.7
Input - watts	: 92W	154W
Speed - r.p.m.	: 15000	10000
Rating - Minutes	: -	5



MODEL NO : SPM 68

	No Load	Full Load
Rated Voltage	: 100F/90A V DC	100F/90A V DC
Current - amps	: 1.1	3.0 MAX
Input - watts	: 99W	270W
Speed - r.p.m.	: 194	184
Rating - Minutes	: 30	30



MODEL NO : PMDC 58 / 59

	No Load	Full Load
Rated Voltage	: 90V DC	90V DC
Current - amps	: 0.2	1
Input - watts	: 25W	90W
Speed - r.p.m.	: 40	38
Rating - Minutes	: Continuous	Continuous



MODEL NO : PMG 2

	No Load	Full Load
Rated Voltage	: 42V DC	42V DC
Current - amps	: 1.1	3.5
Input - watts	: 40W	130W
Speed - r.p.m.	: 200	180
Drive Load Dia	: 40 mm	40 mm

(Also available in 12V/24V/36V/42V/110V)



MODEL NO : PMG 3

	No Load	Full Load
Rated Voltage	: 24V DC	24V DC
Current - amps	: 1.1	5.5
Input - watts	: 40W	130W
Speed - r.p.m.	: 270	230
Rating - Minutes	: 40 mm	40 mm

(Also available in 12V/24V/36V/42V/110V)



MODEL NO : PMG 20

	No Load	Full Load
Rated Voltage	: 12V DC	12V DC
Current - amps	: 1.1	4.0
Input - watts	: 13W	48W
Speed - r.p.m.	: 48/56	37/43
Rating - Minutes	: Continuous	Continuous
Torque	: -	32 Kgs-cm



MODEL NO : PMG 26

	No Load	Full Load
Rated Voltage	: 12V DC	12V DC
Current - amps	: 1.1	4.0
Input - watts	: 13W	48W
Speed - r.p.m.	: 48/56	37/43
Rating - Minutes	: Continuous	Continuous
Torque	: -	32 Kgs-cm



MODEL NO : UM 4B

	No Load	Full Load
Rated Voltage	: 220V AC/DC	220V AC/DC
Current - amps	: 0.8	1.5 / 1.7
Input - watts	: 100W	700W
Speed - r.p.m.	: 27000	8000
Rating - Minutes	: 3	3



MODEL NO : UM 15

	No Load	Full Load
Rated Voltage	: 220V 110V	220V 110V
Current - amps	: 0.65 1.30	1.6 3.2
Input - watts	: 120W 120W	430W 430W
Speed - r.p.m.	: 20000 20000	7000 7000
Rating - Minutes	: - -	Short Duty Short Duty
Torque	: - -	2.5kg-cm 2.5kg-cm



MODEL NO : UM 26

	No Load	Full Load
Rated Voltage	: 220V	220V
Current - amps	: 0.8	1.1
Input - watts	: 100W	200W
Speed - r.p.m.	: 29000	20000
Rating - Minutes	: 1min.	1 min.



MODEL NO : UMG 5

	No Load	Full Load
Rated Voltage	: 220/110V DC	220/110V DC
Current - amps	: 0.4/0.5	0.7/1.0
Input - watts	: 90/60W	150W
Speed - r.p.m.	: 420/260	320/170
Rating - Minutes	: 1	1



MODEL NO : UMG 27

	No Load	Full Load
Rated Voltage	: 220/110V AC/DC	220/110V AC/DC
Current - amps	: 0.58/0.64	1.3/1.6
Input - watts	: 125/70W	290/175W
Speed - r.p.m.	: 640/430	365/200
Rating - Minutes	: 1	1



MODEL NO : UMG 14

	No Load	Full Load
Rated Voltage	: 220V DC 110V	220V DC 110V
Current - amps	: 0.6 1.2	1.2 2.4
Input - watts	: - -	18W 18W
Speed - r.p.m.	: 19 19	17 17



MODEL NO : UMG 31/32 [FOR CLOCKWISE/ANTI CLOCKWISE]

	No Load	Full Load
Rated Voltage	: 230V AC/DC	230V AC/DC
Current - amps	: 1.35	2.7
Input - watts	: 150W	300W
Speed - r.p.m.	: 700	300

WHEEL



CUT-OFF WHEEL DOUBLE NET

Dimension : 355MM X 2.8MM X 25.4MM
 Colour : Brown
 Type : Double Net
 Part No : 3340.I.11.2
 Master Box : (2 bundles of 25 nos each)



CUT-OFF WHEEL SINGLE NET

NEW
 Dimension : 355MM X 2.8MM X 25.4MM
 Colour : Black
 Type : Single Net
 Part No : 3340.I.11.1

CUTTER



ANNULAR CUTTER TYPE : TCT

Size
 In Dia : 12mm to 100mm
 In Depths : 35mm/50mm/75mm/110mm



ANNULAR CUTTER TYPE : HSS

Size
 In Dia : 12mm to 100mm
 In depths : 35mm/50mm/75mm/110mm

CHISELS



CHISELS (FLAT & POINTED) USE FOR : HAMMER

Suitable For	Model No	Description
26mm ROTARY HAMMER	RCP14250	: POINT CHISEL 14x250P
5 Kg DEMOLITION HAMMER	RCF14250	: FLAT CHISEL 14x250F
11Kg DEMOLITION HAMMER	RCF17280	: POINT CHISEL 17x280P
15kg/16kg DEMOLITION HAMMER	RCF18400	: FLAT CHISEL 18x400F
	RCF30400	: POINT CHISEL 30x400
	RCF30400	: FLAT CHISEL 30x400



CHISELS USE FOR : AIR TOOLS

Suitable For : Air Tools

BLADES



TCT BLADES 4" 30T | 40T MODEL NO : RWC11030 | RMC11040

NEW

Size : 4" inch
 Specifications 30T : 110 x 1.6/1.0 x 30T x 20/16mm
 Specifications 40T : 110 x 1.6/1.0 x 40T x 20/16mm
 Usage : Wood
 Suitable For : Wood Work & DIY Projects



TCT BLADES 5" 30T | 40T MODEL NO : RWC12530 | RMC12540

NEW

Size : 5" inch
 Specifications 30T : 125 x 1.8/1.2 x 30T x 20/16mm
 Specifications 40T : 125 x 1.8/1.2 x 40T x 20/16mm
 Usage : Wood
 Suitable For : Wood Work & DIY Projects

SHAFT



FLEXIBLE SHAFT TYPE : 10 FD

Suitable For : FF2 & FSG2 (Shaft Grinder)
 Part No. : 881.3.24

ATTACHMENT



INTERNAL GRINDING ATTACHMENT MODEL NO : IGA

Suitable for : GL3

ACCESSORIES

VIBRATION ROD



VIBRATION ROD

Sizes : 1.5 meter | 3 meter
Part No. : 3503.3.01 | 3503.3.02

MICRO FIBER CLOTH



MICRO FIBER CLOTH

MODEL NO : RMC - 4060

NEW

GSM : 350
Size (mm) : 40cm x 60cm
Type : Micro Fiber
Colours : Multi-colours
Usage : Multi-Purpose

STAND



MAGNETIC STAND MODEL NO : MS

Base : HEXAGONAL
Suitable for : WDH/WDHC/WDH12/WDHC12/
(Mounting) NW8/NW10



MAGNETIC STAND MODEL NO : MS 10

Base : ROUND
Suitable for : WDH/WDHC/WDH12/WDHC12/
(Mounting) NW8/NW10



MAGNETIC STAND MODEL NO : MS 50

Base : RECTANGULAR
Suitable for : WDH/WDHC/WDH12/WDHC12/
(Mounting) NW8/NW10



MECHANICAL STANDS MODEL NO : ES 1, ES 3, ES 14 & ES 23

Model	Description
ES1	WDH / WDHC WITH MS10
ES3	NW10 / NW8 WITH MS10
ES14	WDH / WDHC WITH MS50
ES23	NW10 / NW8 WITH MS10



ACCESSORIES



SALES NETWORK (INTERNATIONAL)

- Nepal



SALES NETWORK (NATIONAL)

- Ahmedabad
- Bangalore
- Bhilai
- Bhopal
- Bhubaneswar
- Calicut
- Chennai
- Coimbatore
- Cuttack
- Faridabad
- Gurgaon
- Guwahati
- Hubli
- Hamirpur
- Indore
- Jaipur
- Jamshedpur
- Jammu
- Kanpur
- Kolkata
- Kolhapur
- Kochi
- Lucknow
- Mumbai
- Madurai
- Nagpur
- New Delhi
- Pune
- Raipur
- Secunderabad
- Siliguri
- Vijayawada
- Vishakhapatnam
- Vadodara
- Varanasi

Ralli Wolf Industries Ltd.

An ISO 9001 : 2015 Certified Organisation

Registered Office : Diamond Heritage, 5th Floor,
16 Strand Road, Kolkata- 700 001, WB, India

Work : G-104, MIDC Area, Ahmednagar – 414111, Maharashtra, India

Phone : 8100080353 | **Email :** customercare@ralliwolf.com

Website : ralliwolf.com

Notes :

- 110V can be made available on select models for MOQ.
- Machines with Deadman switches are available on request for certain models.
- Oil lubrication is must for all the tools before starting the operation.

*The Pictures and Specification are only for reference.



Due to continuous R & D, Product supplied may differ the data contained herein.
The catalogue supercedes all earlier catalogues.

Follow us:

