



ERGONOMIC
HANDLES



50 µm HARD
ANODIZED
DOVE TAIL
SLIDE SYSTEM



STRONG
MAGNET

SPECIFICATIONS

Motor power	1200 watt
Spindle	19 mm (3/4") Weldon
Broach cutter (35mm length)	Ø12 mm - Ø40mm
Broach cutter (50mm length)	Ø12 mm - Ø40 mm
Twist Drill	Upto Ø13 mm
RPM	450 min ⁻¹
Weight	12 kg (26,8 lbs)
Magnet power	10000 N
Input supply voltage	220v-240v
Frequency	50Hz-60Hz

SWC 40 PRO

Magnet-Kernbohrmaschinen
Magnetic Core Drilling Machine



SMARTLY MOUNTED COOLANT SYSTEM



STANDARD ACCESSORIES



Allen Key 2.5, 4, 6

Pilot Pin 6x50, 8x50

Safety Belt



SWC 50 MAX-PRO

Magnet-Kernbohrmaschinen Magnetic Core Drilling Machine



ERGONOMIC
HANDLES



50 µ HARD
ANODIZED
DOVE TAIL
SLIDE SYSTEM



STRONG
MAGNET



SMARTLY MOUNTED COOLANT SYSTEM

SPECIFICATIONS

Motor power	1350 watt
Spindle	MT 3, 19mm (3/4") Weldon
Broach cutter (35mm length)	Ø12 mm - Ø50mm
Broach cutter (50mm length)	Ø12 mm - Ø50 mm
Twist Drill	Upto Ø18 mm
RPM	n250 min ⁻¹ -n450 min ⁻¹
Weight	12 kg (26,8 lbs)
Magnet power	11000 N
Input supply voltage	220v-240v
Frequency	50Hz-60Hz



STANDARD ACCESSORIES





SWC 32 PRO

Magnet-Kernbohrmaschinen Magnetic Core Drilling Machine



ERGONOMIC
HANDLES



50 H HARD
ANODIZED
DOVE TAIL
SLIDE SYSTEM



SPECIFICATIONS

Motor power	1100 watt
Spindle	19 mm (3/4") Weldon
Broach cutter (35mm length)	Ø12 mm - Ø35 mm
Broach cutter (50mm length)	Ø12 mm - Ø35 mm
RPM	450 min ⁻¹
Weight	10 kg (22,0 lbs)
Magnet power	10000 N
Input supply voltage	220v-240v
Frequency	50Hz-60Hz



STANDARD ACCESSORIES

